

6" ELS - Marbella Plus | LED RECESSED DOWNLIGHT 5 COLOURS IN 1

Product Description

Reliable Quality: This IC rated downlight is permitted to be in contact with combustible material

Body:

Durable airtight aluminum body with UV stable paint and white PMMA diffuser lens for low glare. Includes silicone gasket for wet location applications. Includes a newly patented designed regressed inner heat dissipation ring, enabling the fixture to keep a smooth, round rear finish. A new 6mm trim adding a luxury finish and curb appeal.

LED Characteristics

This general application light fixture features a 12 watt (for 6") LED module that maintains uniform intensity producing up to 1150 lumens, with a typical CRI of 90. Available with 5 step CCT switch (2700K, 3000K, 3500K, 4000K and 5000K) or Wall Switch on "SW" Mode.

Beam Spread

The fixture lens provides 120° beam spread.

Quick Connect push-in terminals

"Quick connect" push-in terminals for quick and easy installation.

Mounting

Includes two spring loaded clips to attach to any ceiling material. The slim profile allows to be mounted under joists or duct work



Applications

Dimming
100%-10% dimming capability. This fixture is compatible with industry standard TRIAC/ELV dimmers.

Operating Temperature
-30°C~40°C (-22°F~104°F)

LED Driver
Extruded aluminum hardwire box with 370mA (for 6") dimmable class II electronic LED driver with 110-135V AC input. Includes an 18' plenum rated FT1 wire with DC 2.1 connector from driver to fixture.



Specification

	Input Power	Lumen Output	Equiv	Size	Power Factor	CCT
ELSDR1606G55WH-12	12W	1150lm	100W	6"	>0.9	2700K/3000K/3500K 4000K/5000K

Input Voltage	Dimmable	Beam Angle	CRI	Application	Materials	Lifespan
AC120V/60Hz	Yes	120degree	>90Ra	WET Location	Aluminum	50,000 Hours

Product Dimensions

